

LUMACORE ACCENT SPOT LIGHT

15300BZ-LMA30K-testMF1

12V VARIABLE OUTPUT LED 3000K

DETAILS	
FINISH:	Bronze
MATERIAL:	Aluminum
GLASS:	Frosted Lens
DIMMABLE:	No

DIMENSIONS	
WIDTH:	4.5"
HEIGHT:	4"
DEPTH:	4.5
WEIGHT:	1lb

LIGHT SOURCE	
LIGHT SOURCE:	LumaCore
WATTAGE:	12w, 8w, 5w,3w LumaCore LED *Included
VOLTAGE:	12v

MOUNTING	
LEAD WIRE:	1 X 18"

SHIPPING	
CARTON LENGTH:	8.7
CARTON WIDTH:	18.9
CARTON HEIGHT:	17.7
CARTON WEIGHT:	2

PRODUCT DETAILS:

- LumaCore Series products carry a lifetime limited warranty
- Incorporates CREE LEDs with application performance tested by CREE
- Suitable for use in wet (outdoor direct rain) locations as defined by NEC and CEC. Meets United States UL Underwriters Laboratories & CSA Canadian Standards Association Product Safety Standards
- Wattage settings includes: 3W (260 Lumens), 5W (350 Lumens), 8W (475 Lumens), 12W (750 Lumens)
- Photometrics based off engine photometrics.
- For more information on how to control your landscape lighting via the Hinkley Home Automation App, [click here](#).
- A wiring kit and ground spike are supplied

HINKLEY

HINKLEY
33000 Pin Oak Parkway
Avon Lake, OH 44012

PHONE: (440) 653-5500
Toll Free: 1 (800) 446-5539

hinkley.com