LUMACORE ACCENT SPOT LIGHT

5536SK-LMA27K

120V VARIABLE OUTPUT LED 2700K

Accentuate your home's architecture and highlight your landscape's natural beauty with a warm ambient glow. Hinkley's Variable Output LumaCORE™ LED Accent Lighting Systems are expertly engineered to withstand the elements and provide complete control over wattage and beam spread. 120V Spotlights are engineered to enhance your entire property with brighter, more powerful illumination.

| DETAILS | |
|-----------|-------------|
| FINISH: | Satin Black |
| MATERIAL: | Aluminum |
| GLASS: | Clear Lens |
| DIMMABLE: | No |

| DIMENSIONS | |
|------------|------|
| WIDTH: | 5.8" |
| HEIGHT: | 3.3" |
| DEPTH: | 2.5 |
| WEIGHT: | 1lb |

| LIGHT SOURCE | |
|---------------|---|
| LIGHT SOURCE: | LumaCore |
| WATTAGE: | 12w, 8w, 5w, 3w LumaCore LED *Included |
| VOLTAGE: | 120v |
| VOLT AMPS: | 12.4, 7.8, 5.3, 3.2 |

| MOUNTING | |
|--------------|---------|
| LEAD WIRE: 1 | 1 X 18" |

| SHIPPING | |
|----------------|------|
| CARTON LENGTH: | 11.5 |
| CARTON WIDTH: | 4.9 |
| CARTON HEIGHT: | 2.8 |
| CARTON WEIGHT: | 1.1 |
| | - |





PRODUCT DETAILS:

- LumaCore Series products carry a lifetime limited warranty
- Incorporates CREE LEDs with application performance tested by CREE
- Suitable for use in wet (outdoor direct rain) locations as defined by NEC and CEC. Meets
 United States UL Underwriters Laboratories & CSA Canadian Standards Association Product
 Safety Standards
- Wattage settings includes: 3W (260 Lumens), 5W (350 Lumens), 8W (475 Lumens), 12W (750 Lumens)
- Photometrics based off engine photometrics.
- Classic lines and heritage details complement traditional architecture
- Three lens options offer versatility in beam spread via an easy to remove and insert assembly includes: 20° Spot, 40° Flood, 60° Flood
- For more information on how to control your landscape lighting via the Hinkley Home Automation App, click here.



PHONE: (440) 653-5500

Toll Free: 1 (800) 446-5539