



PRODUCT DETAILS:

- Wiring and surface mount kit are supplied
- Suitable for use in wet (outdoor direct rain) locations as defined by NEC and CEC. Meets
 United States UL Underwriters Laboratories & CSA Canadian Standards Association Product
 Safety Standards
- Photometrics based off engine photometrics.
- For more information on how to control your landscape lighting via the Hinkley Home Automation App, click here.
- Equipped with a 120/277 universal driver. 0-10 dimming.
- Bold lines and a clean, minimalist style complement contemporary architecture
- LED integrated components carry a 10-year limited warranty

TAPER

15288BZ

LED BOLLARD

Sleek and sophisticated, Taper is built to last with a timeless, minimalist style that radiates contemporary cool. Its recessed integrated LEDs are directed downward with gradient illumination that grazes the gently sloped design.

DETAILS	
FINISH:	Bronze
MATERIAL:	Aluminum
	YES - CL TYPE DIMMER (SSL7A)

DIMENSIONS	
WIDTH:	6"
HEIGHT:	36"
DEPTH:	6
WEIGHT:	16.5lb

LIGHT SOURCE	
LIGHT SOURCE:	Integrated LED
WATTAGE:	28w LED *Included
VOLTAGE:	120v/277v

MOUNTING	
LEAD WIRE:	1 X 6"

SHIPPING	
CARTON LENGTH:	10
CARTON WIDTH:	10
CARTON HEIGHT:	41
CARTON WEIGHT:	18.6

