

# LUMACORE ACCENT SPOT LIGHT

## 1535BZ-LMA30K

12V VARIABLE OUTPUT LED 3000K WITH LONG COWL

Accentuate your home's architecture and highlight your landscape's natural beauty with a warm ambient glow. Hinkley's Variable Output LumaCORE™ LED Accent Lighting Systems are expertly designed to withstand the elements and provide complete control over wattage and beam spread.

DETAILS	
FINISH:	Bronze
MATERIAL:	Aluminum
GLASS:	Clear Lens
DIMMABLE:	No

DIMENSIONS	
WIDTH:	9.8"
HEIGHT:	3.3"
DEPTH:	2.5
WEIGHT:	1.4lb

LIGHT SOURCE	
LIGHT SOURCE:	LumaCore
WATTAGE:	12w, 8w, 5w, 3w LumaCore LED *Included
VOLTAGE:	12v
VOLT AMPS:	12.4, 7.8, 5.3, 3.2
TRANSFORMER REQUIRED:	Yes

MOUNTING	
LEAD WIRE:	1 X 18"

SHIPPING	
CARTON LENGTH:	10
CARTON WIDTH:	5
CARTON HEIGHT:	5
CARTON WEIGHT:	2



**ENGINEERED TO WITHSTAND THE ELEMENTS**

HEAT      WATER  
SNOW + ICE      IMPACT

**THREE LENSES INCLUDED**

**MATCH YOUR BEAM WIDTH TO YOUR APPLICATION**



### PRODUCT DETAILS:

- LumaCore Series products carry a lifetime limited warranty
- Incorporates CREE LEDs with application performance tested by CREE
- Suitable for use in wet (outdoor direct rain) locations as defined by NEC and CEC. Meets United States UL Underwriters Laboratories & CSA Canadian Standards Association Product Safety Standards
- Wattage settings includes: 3W (260 Lumens), 5W (350 Lumens), 8W (475 Lumens), 12W (750 Lumens)
- Photometrics based off engine photometrics.
- Three lens options offer versatility in beam spread via an easy to remove and insert assembly - includes: 20° Spot, 40° Flood, 60° Flood
- For more information on how to control your landscape lighting via the Hinkley Home Automation App, [click here](#).
- A wiring kit and ground spike are supplied