

LUMACORE ACCENT SPOT LIGHT

15300SK-LMA27K

12V VARIABLE OUTPUT LED 2700K

Accentuate your home's architecture and highlight your landscape's natural beauty with a warm ambient glow. Hinkley's Variable Output LumaCORE™ LED Accent Lighting Systems are expertly designed to withstand the elements and provide complete control over wattage and beam spread.

| DETAILS | |
|-----------|--------------|
| FINISH: | Satin Black |
| MATERIAL: | Aluminum |
| GLASS: | Frosted Lens |
| DIMMABLE: | No |

| DIMENSIONS | |
|------------|------|
| WIDTH: | 4.5" |
| HEIGHT: | 4" |
| DEPTH: | 4.5 |
| WEIGHT: | 1lb |

| LIGHT SOURCE | |
|---------------|--|
| LIGHT SOURCE: | LumaCore |
| WATTAGE: | 12w, 8w, 5w,3w LumaCore LED *Included |
| VOLTAGE: | 12v |
| VOLT AMPS: | 12.4, 7.8, 5.3, 3.2 |

| MOUNTING | |
|------------|---------|
| LEAD WIRE: | 1 X 18" |

| SHIPPING | |
|----------------|------|
| CARTON LENGTH: | 8.7 |
| CARTON WIDTH: | 18.9 |
| CARTON HEIGHT: | 17.7 |
| CARTON WEIGHT: | 2 |
| | - |







PRODUCT DETAILS:

- LumaCore Series products carry a lifetime limited warranty
- Incorporates CREE LEDs with application performance tested by CREE
- Suitable for use in wet (outdoor direct rain) locations as defined by NEC and CEC. Meets
 United States UL Underwriters Laboratories & CSA Canadian Standards Association Product
 Safety Standards
- Wattage settings includes: 3W (260 Lumens), 5W (350 Lumens), 8W (475 Lumens), 12W (750 Lumens)
- Photometrics based off engine photometrics.
- For more information on how to control your landscape lighting via the Hinkley Home Automation App, click here.
- · A wiring kit and ground spike are supplied



PHONE: (440) 653-5500

Toll Free: 1 (800) 446-5539